

S6-40



Speed-Cap



S6-3055Z



S6-5

### SHAKESPEARE ELLIPSOIDAL SPOTS:


These are state of the art luminaries in function, style, and efficiency. The dichroic coated glass elliptical reflector reduces heat in the light beam, resulting in longer gel and pattern life while offering a sharp, full light field and distortion free pattern projection. Rear section has easy focus Speed-Cap with medium 2-pin socket. Front section rotates up to 180 degrees to adjust alignment of shutters or pattern gobos. Large accessory slot with door for use with optional drop-in iris and rotating gobo devices. Front color frame holder has 2 slots and safety latch. Interchangeable lens barrels for the fixed focus models. Dual locking dogs on yoke. Rear ring handle also serves to wrap power cord. UL listed for maximum of 750 watts. Typically used with 575 watt (GLC or GLA) or 750 watt HX754 or HX655 lamps. Includes color frame, 3 ft. cord, and safety cable. Altman brand.

Catalog No.	Description	Price
S6-	Shakespeare fixed focus ellipsoidal spot (specify -50°, -40°, -30°, or -20° model).....	\$ 273.75
S6-10	Shakespeare long throw 10° ellipsoidal spot....	\$ 375.00
S6-5	Shakespeare long throw 5° ellipsoidal spot....	\$ 468.75
S6-1535Z	Shakespeare variable focus 15°-35° ellip. spot.	\$ 401.25
S6-3055Z	Shakespeare variable focus 30°-55° ellip. spot.	\$ 401.25

### Accessories for Shakespeare spots:

Cat. #	Price	Description	Accessories for Shakespeare models				
			50° - 20°	10°	5°	S6-Zoom	
CF-4.5	\$ 2.93	Color frame 6-1/4" x 6-1/4"	incl.				
CF-06	\$ 2.93	Color frame 7-1/2" x 7-1/2"					incl.
CF-10	\$ 7.80	Color frame 12" x 12"		incl.			
CF-12	\$ 10.14	Color frame 14" x 14"			incl.		
510	\$ 11.51	Clamp, malleable iron	opt.				
510-HD	\$ 22.62	Clamp, heavy duty mal. iron				opt.	
SC-36-BK	\$ 4.29	Safety cable, black with snap				incl.	
DN-4.5	\$ 6.24	Donut with 2-1/2" hole	opt.				
DN-06	\$ 6.63	Donut with 3" hole					opt.
DN-10	\$ 15.60	Donut with 5" hole		opt.			
DN-12	\$ 23.40	Donut with 6" hole			opt.		
SN-4.5	\$ 13.65	Snoot fits 6-1/4" x 6-1/4" holder	opt.				
SN-6	\$ 16.38	Snoot fits 7-1/2" x 7-1/2" holder					opt.
SN-10	\$ 25.35	Snoot fits 12" x 12" holder		opt.			
SD-II	\$ 60.00	Drop-in iris					
360-PH	\$ 5.85	Pattern holder, channel style					
R15786	\$ 15.95	Universal iris slot holder for 1 or 2 glass or metal gobos.	Optional, fits all Shakespeare models				
S6G-PH	\$ 11.70	Pattern holder, for glass, fits into "drop-in" iris slot.					

"incl." = included with spot, "opt." = optional



### Lamps for Shakespeare spots:

Cat. No.	Price	Watts	Hours	Color Temp.	Rated Lumens
GLC/HX604	\$ 21.13	575	400	3200K	15,700
GLA/HX605	\$ 22.15		1500	3050K	13,600
HX754	\$ 20.80	750	300	3200K	20,500
HX755	\$ 22.75		1500	3050K	18,250



SN-Snoot



R15786 holder



360-PH pattern holder



510 Clamp



510-HD Clamp



DN-Donut

### Fixed focus models:

Model#	Light Angle	Using GLC 575 Watt lamp								
		Distance	10	20	30	40	50	60	70	80
S6-50	50°	Field Dia.	10	19	28	38	47	56	66	76
		Intensity	463	116	51	29	19	13	9	7
		Field Dia.	7	14	21	28	35	42	48	55
S6-40	40°	Field Dia.	5	10	15	20	25	30	35	41
		Intensity	981	245	109	61	39	27	20	15
		Field Dia.	4	7	11	14	18	22	25	29
S6-30	30°	Field Dia.	4	7	11	14	18	22	25	29
		Intensity	1493	373	166	93	60	41	30	23
		Field Dia.	4	7	11	14	18	22	25	29
S6-20	20°	Field Dia.	4	7	11	14	18	22	25	29
		Intensity	1897	474	211	119	76	53	39	30
		Field Dia.	4	7	11	14	18	22	25	29

Distance & Field Dia. in feet. Peak Intensity in foot-candles.

### Variable focus models:

Include adjustable focus front lens assembly for variable size beam spread.

Model#	Light Angle	Using GLC 575 Watt lamp								
		Distance	10	20	30	40	50	60	70	80
S6-1535Z	15°	Field Dia.	3	5	7	10	12	15	17	20
		Intensity	1660	415	184	104	66	46	34	26
		Field Dia.	6	12	18	24	30	36	42	48
	35°	Field Dia.	543	136	60	34	22	15	11	8
		Intensity	1897	474	211	119	76	53	39	30
		Field Dia.	5	10	15	20	25	30	36	41
S6-3055Z	30°	Field Dia.	5	10	15	20	25	30	36	41
		Intensity	1660	415	184	104	66	46	34	26
		Field Dia.	10	20	30	40	49	59	69	79
	50°	Field Dia.	543	136	60	34	22	15	11	8
		Intensity	1897	474	211	119	76	53	39	30
		Field Dia.	5	10	15	20	25	30	36	41

Distance & Field Dia. in feet. Peak Intensity in foot-candles.

### Long throw models:


For distances of 80 to 150 feet have larger front lenses.

Model#	Light Angle	Using GLC 575 Watt lamp									
		Distance	80	90	100	110	120	130	140	150	
S6-10	10°	Field Dia.	14	16	17	19	21	23	24	26	
		Intensity	124	98	79	65	55	47	40	35	
		Field Dia.	10	11	12	13	15	16	17	18	
S6-5	5°	Field Dia.	152	120	97	81	68	58	50	43	
		Intensity	1897	474	211	119	76	53	39	30	
		Field Dia.	10	11	12	13	15	16	17	18	

Distance & Field Dia. in feet. Peak Intensity in foot-candles.

### Dimensions:

Dimensions shown in inches. Hanging yoke has two sets of mounting holes, so "B" and "E" show 2 lengths. Normal position allows fixture to swing past yoke. Second position is for hanging fixture closer to clamp.



Model #	Dimensions					Wgt.*	Color Frame
	A	B	C	D	E		
S6-20 to 50	24" - 26 1/4"	17" or 13 1/2"	12"	9 1/4"	11" or 7 1/2"	15#	6 1/2" x 6 1/2"
S6-1535Z	30"	17" or 13 1/2"	12"	9 1/4"	11" or 7 1/2"	21#	7 1/2" x 7 1/2"
S6-3055Z	24 3/4"	17" or 13 1/2"	12"	9 1/4"	11" or 7 1/2"	22#	7 1/2" x 7 1/2"
S6-10	29 1/4" - 31 1/2"	17" or 13 1/2"	11	9 1/4"	11" or 7 1/2"	16#	12" x 12"
S6-5	22.87	18 1/4" or 14 1/2"	17	9 1/4"	11" or 7 1/2"	17#	14" x 14"

\* Wgt. = hanging weight